



## Evaluating linear recursive filters on clusters of workstations

Przemysław Stpiczyński\*

*Department of Computer Science, Maria Curie-Skłodowska University,  
pl. M. Curie-Skłodowskiej 1, 20-031 Lublin, Poland*

### Abstract

The aim of this paper is to show that the recently developed high performance algorithm for solving linear recurrence systems with constant coefficients together with the new BLAS-based algorithm for narrow-banded triangular Toeplitz matrix-vector multiplication allow to evaluate linear recursive filters efficiently, even on clusters of workstations. The results of experiments performed on a cluster of twelve Linux workstations are also presented. The performance of the algorithm is comparable with the performance of two processors of Cray SV-1 for such kind of recursive problems.

### 1. Introduction

Let us consider the following problem of evaluating linear recursive filters which is very popular in signal processing [1]. For a given sequence of real numbers  $x_1, x_2, \dots, x_n$  called input signals, we have to evaluate an output sequence  $y_1, y_2, \dots, y_n$ , satisfying

$$y_k = \sum_{j=1}^m b_j y_{k-j} + \sum_{j=0}^m a_j x_{k-j}, \quad (1)$$

where  $x_k = 0$ ,  $z_k = 0$  for  $k \leq 0$  and coefficients  $a_j$ ,  $b_j$  are calculated using  $z$ -transforms [1]. Unfortunately, the problem has “recursive” nature and simple routines based on (1) do not fully utilize the underlying hardware, i.e. memory hierarchies and multiple processors, and they achieve poor performance. On the other hand, our problem is a typical example of how the speed of the slowest parts of programs influences the overall performance (so called *Amdahl's law* [2]). Thus, it is clear that efficient high performance algorithms for solving our problem should be designed.

It is well known that reducing costs of memory access is essential for achieving good performance of numerical software [3]. Usually, codes based on Level 2 and 3 BLAS (Basic Linear Algebra Subprograms [2]) routines achieve

---

\* *E-mail address:* [przem@hektor.umcs.lublin.pl](mailto:przem@hektor.umcs.lublin.pl)





that each processor holds (or calculates) coefficients  $a_0, \dots, a_m$  and  $b_1, \dots, b_m$ . Also, each processor holds  $r/p$  columns of the matrix  $X$ , where  $p$  is the number of available processors. The first stage of the algorithm requires communication, namely each processor (except for the last one) sends  $m$  last entries of its last column of the block of  $X$  to its “left” neighbour. The details of the second stage of the algorithm can be found in [7].

It is obvious that the performance of the algorithm depends on the choice of the parameters  $s$  and  $r$ . The second stage is more complicated thus it is clear that the parameters should be chosen to minimize the cost of that stage. To predict the behaviour of the algorithm for solving (3), we have observed [7] that its complexity can be expressed in terms of Bulk Synchronous Parallel Architecture (BSP for short [9]). In this model, a parallel program consists of a number of supersteps. Each superstep comprises local computations, global data exchange and the barrier synchronization (see Figure 1).




Fig. 1. BSP architecture

The BSP model is characterized by the following parameters:  $p$ , the number of available processors,  $g$ , the time (in flop time units) it takes to communicate (send or receive) a data element and  $l$ , the time (in flop time units) it takes all processors to synchronize. The complexity of a superstep is defined as

$$w_{\max} + gh_{\max} + l$$

where  $w_{\max}$  is the maximum number of flops performed, and  $h_{\max}$  is the number of messages sent or received by any one processor during this superstep.

To find the optimal value of  $s$ , we minimize the BSP cost of the “most time consuming” steps of the algorithm, namely

$$2m \left( s - \frac{m+1}{2} \right) \left( \frac{n}{sp} + 1 \right) + 3m^2 \frac{n}{s} + mg(p-1) + lp \tag{8}$$

and because the value of  $s$  should be integer, we get

$$s^* = \left\lfloor \sqrt{\frac{n(3mp - m - 1)}{2p}} \right\rfloor. \tag{9}$$

Thus we can conclude that for the algorithm, the optimal choice of the value of the parameter  $s$  does not depend on the BSP parameters. So we can expect that the choice (9) will be good for a wide variety of BSP architectures and the formula (9) can be included in the source code of the algorithm.

#### 4. Results of experiments

The algorithm has been tested on a cluster of twelve 667 MHz Pentium III workstations running under Linux operating system for various problem sizes ( $n$ ,  $m$ ) and the number of processors ( $p$ ). The results of experiments can be summarized as follows.




Fig. 2. The performance of the algorithm

1. The algorithm achieves the best performance for the values of  $s=0.5s^*$ . The performance of the algorithm depends strictly on the performance of the BLAS routines (which is not taken into account in BSP) and for such values of  $s$  we achieve “the perfect balance” between the BSP cost and the

efficiency of the BLAS routines. When  $s=s^*$ , then the matrices are too narrow.

2. The performance of the algorithm (in Mflops) grows when the problem sizes ( $n, m$ ) and the number of processors grow. However the performance of simple serial algorithm based on (1) also grows when  $m$  grows. Thus we can observe that the speedup is almost constant when  $m$  grows. For  $p=12$ , the speedup of the algorithm is up to 15.
3. When  $p=12$ , then the performance of the algorithm (in Mflops) is up to 2200 Mflops, which is comparable with the performance of two processors of Cray SV-1 [6] for solving such a kind of recursive problems.

### Acknowledgments

The work has been developed within task WP14 of 6 T11 2003 C/06098 “CLUSTERIX - The national Linux Cluster”.

### References

- [1] Smith S.W., *The Scientist and Engineer's Guide to Digital Signal Processing*, California Technical Publishing, San Diego, CA, (1997).
- [2] Dongarra J., Duff I., Sorensen D., Van der Vorst H., *Solving Linear Systems on Vector and Shared Memory Computers*, SIAM, Philadelphia, (1991).
- [3] Dongarra J., Hammarling S., Sorensen D., *Block reduction of matrices to condensed form for eigenvalue computations*, J. Comp. Appl. Math, 27 (1989) 215.
- [4] Baker A., Dennis J., Jessup E.R., *Toward memory-efficient linear solvers*, Lecture Notes in Computer Science, 2565 (2003) 315.
- [5] Stpiczyński P., *Solving linear recurrence systems using level 2 and 3 BLAS routines*, Lecture Notes in Computer Science, 3019 (2004) 1059.
- [6] Stpiczyński P., *Numerical evaluation of linear recurrences on various parallel computers*. In M.Kovacova, editor, Proceedings of Aplimat 2004, 3<sup>rd</sup> International Conference, Bratislava, Slovakia, (2004) 889.
- [7] Stpiczyński P., *Numerical evaluation of linear recurrences on high performance computers and clusters of workstations*, In Proceedings of PARELEC 2004, International Conference on Parallel Computing in Electrical Engineering. IEEE Computer Society Press, (2004).
- [8] Pacheco P., *Parallel Programming with MPI*, Morgan Kaufmann, San Francisco, (1996).
- [9] Hill J., Donaldson S., Skillicorn D., *Portability of Performance with the BSPlib Communications Library*, In Programming Models for Massively Parallel Computers, (MPPM'97), London, IEEE Computer Society Press, (1997).